

Overview

C8/80/22 is an alternative mild steel stock fence to C8/80/15, with 22cm between the vertical stay wires. This increased distance between verticals helps prevent sheep getting their heads stuck in the fence. Mild steel does not need to be strained as tightly as the high tensile variant and gradual turns can be made off intermediate posts. This is particularly useful if you need to make a lot of turns in your fence.

Compliance with British and European Standards

BSEN 10218 - Steel Wire and Wire Products part 2 - General Wire Dimensions and Tolerances.

BSEN 10223 - Steel Wire and Wire Products for Fencing and Netting part 5 - Steel Wire Woven Hinged Joint and Knotted Mesh Fencing.

BSEN 10244 - Steel Wire and Wire Products Non-ferrous Metallic Coatings on Steel Wire part 2 - Zinc or Zinc Alloy Coatings (all Tornado products galvanised to class A).

Sustainability

All Tornado products are 100% recyclable.

Traceability

This fence is batch marked and can be traced back to point of manufacture.

Installation Guidelines

A straining post is required at every major change in direction or any termination and should be supported by a strut or box assembly. Netting should be tied off on the straining posts by hand or with suitable joiners. When tensioning the fence the 'crimp' in the net should be reduced by approx: 50%. Avoid driving staples tight against the wire as this will damage the galvanised coating. Two strands of barbed wire or a single electrified wire can be added to the top of the fence.

Health and Safety

It is recommended that safety gloves, boots and glasses are worn at all times when handling the product.

Suitable for

- All Livestock

Specification



No. of Line Wires	8
Overall Height (cm)	80
Distance between stay wires (cm)	22
Top & bottom line wire specification	3mm dia - 695-850 N/mm ²
Intermediate line wire specification	2.5mm dia - 695-850 N/mm ²
Vertical stay wire specification	2.5mm dia - 695-850 N/mm ²
Average Weight per 50 Metre Roll (kg)	26.98
Material Composition	Heavily galvanised steel wire

Product Codes

MZCG088008	50 metre roll
MZCG088022	100 metre roll
MZCG088021	250 metre roll
MZCG088023	500 metre roll



All measurements are approximate. It is the user's responsibility to check the product is suitable for the application. We reserve the right to change specifications without notification.

Top wire 3mm mild steel
 Intermediate line wire 2.5mm mild steel
 Vertical stay wire 2.5mm



Information on ancillary items and tools can be found on the relevant data sheets.

Fence Configuration Detail



Hinge Joint

Traditional cost effective joint. Enables the netting to be turned out or cranked for use in special applications.

Related Products

- Plain wire
- Staples
- Netting clips
- Range of fence installation tools