

Overview

L13/122/15 is a lightweight, mild steel stock fence, ideal for saving money when used in areas of low pressure from livestock or for a short term project. Mild steel does not need to be strained as tightly as the high tensile variant and gradual turns can be made off intermediate posts. This is particularly useful if you need to make a lot of turns in your fence.

Compliance with British and European Standards

BSEN 10218 - Steel Wire and Wire Products part 2 - General Wire Dimensions and Tolerances.

BSEN 10223 - Steel Wire and Wire Products for Fencing and Netting part 5 - Steel Wire Woven Hinged Joint and Knotted Mesh Fencing.

BSEN 10244 - Steel Wire and Wire Products Non-ferrous Metallic Coatings on Steel Wire part 2 - Zinc or Zinc Alloy Coatings (all Tornado products galvanised to class A).

Sustainability

All Tornado products are 100% recyclable.

Traceability

This fence is batch marked and can be traced back to point of manufacture.

Installation Guidelines

A straining post is required at every major change in direction or any termination and should be supported by a strut or box assembly. Netting should be tied off on the straining posts by hand or with suitable joiners. When tensioning the fence the 'crimp' in the net should be reduced by approx: 50%. Avoid driving staples tight against the wire as this will damage the galvanised coating. Two strands of barbed wire or a single electrified wire can be added to the top of the fence.

Health and Safety

It is recommended that safety gloves, boots and glasses are worn at all times when handling the product.

Suitable for

- Sheep
- Plantations

Specification

No. of Line Wires	13
Overall Height (cm)	122
Distance between stay wires (cm)	15
Top & bottom line wire specification	2.5mm dia - 695-850 N/mm ²
Intermediate line wire specification	2mm dia - 695-850 N/mm ²
Vertical stay wire specification	2mm dia - 695-850 N/mm ²
Average Weight per 50 Metre Roll (kg)	32.46
Material Composition	Heavily galvanised steel wire

Product Codes

MZLG131201	50 metre roll
------------	---------------

All measurements are approximate. It is the user's responsibility to check the product is suitable for the application. We reserve the right to change specifications without notification.

